

APTI-14C2-36W



ONVIF 2.0 yhteensopiva pienikokoinen alumiinirunkoinen megapikselikamera (1.3 Mpix 1280x960)

Selain:

Internet Explorer
Google Chrome + IE Tab

Tallennusohjelmistot:

Kameran mukana (CD:llä)
iSpy (testattu, ladattavissa verkosta, ilmainen)
Kaikki ONVIF 2.0 yhteensopivat (ei testattu)

Virransyöttö:

12V (virtalähde mukana)
POE (tarvitsee POE-splitterin 48/12V)

Huomaa: Netcam Watcher Pro ei tue tätä kameraa

Tarvikkeet:



- CD
- kiinnitusruuvit + proput
- kuusiokoloavain
- RJ45-liittimen sääsuoja

SPECIFICATIONS

Standard: TCP/IP

Sensor: 1/3 " Sony CMOS IMX225

Digital Image Processor: Hisilicon 3518C

Matrix size: 1.3 Mpx

Resolution: 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p

Operation modes: The main and sub streams can only occur in the configurations shown below :

Firmware 3518C+IMX225_X_5.1.17.5

- Main stream : 1280 x 960 + Sub stream : 720 x 480
- Main stream : 1280 x 720 + Sub stream : 720 x 480

Lens: 3.6 mm - 2.0 Mpx View angle:

- 67 °

S/N ratio: > 50 dB

Range of IR illumination: 20 m

IR illuminator power adjustment: Automatic

Compression: H.264 Bitrate: 64 ... 12000 kbit/s

Main stream frame rate: max. 25 fps - 1080p

Network interface: 10/100 Base-T (RJ-45)

Network protocols: RTSP, FTP, DDNS, NTP, TCP

WEB Server: Built-in - port 80

Max. number of on-line users: 10

ONVIF: 2.0 - port 8999

Audio: --

Mobile phones support:

RS-485 interface: --

Alarm inputs / outputs: --

Main features:

- ICR - Movable InfraRed filter
- Possibility to change the resolution, quality and bit rate
- Motion Detection
- Privacy zones
- Configurable: brightness, contrast, saturation
- Sharpness - sharper image outlines
- Mirror - Mirror image
- Day/night mode

Power supply: 12 V DC / 520 mA

Housing: Metal

Color: White

Supported languages: English

"Index of Protection": IP66

Operation temp: -20 °C ... 55 °C

Weight: 0.37 kg

Dimensions: Ø 67 x 133 mm

Guarantee: 2 years